

Ketel NXR 3



Hulp voor brander keuze



Type	Brander Keuze	Brander vermogen (kW)	Verstuiver Danfoss USG	Pompdruk (bar)	Indicatief luchtklep regeling	Positie van de vlamkop (maat X mm)	Indicatief vlamkop positie
NXR 3-34 70 - 90 kW	OES 255 LE	75	1,50/45°S	11,5	90	41	10
		90	1,75/45°S	13,6	110	39,5	8,5
		105	2,00/45°S	14	150	34	3
NXR 3-35 90-130 kW	OES 352 LE	80	1,65/45°S	13,5	12	54	33
		100	2,00/45°S	13,5	15	51	30
		120	2,50/45°S	12,5	20	49	28
		140	3,00/45°S	11	26	46	25
NXR 3-36 130-170 kW	OES 353 LZ	155	2,50/45°S	12,5/22,5	15/22	48	33
		175	2,75/45°S	10,5/21	14/24	45	30
		205	3,50/45°S	11,0/20,0	20/34	28	43
NXR 3-37 170-210 kW	OES 354 LZ	195	3,00/45°S	10,0/23,5	12/25	61	32
		210	3,50/45°S	9,5/21,0	13/28	59	30
		230	4,00/45°S	12,5/21,5	21/37	57	28
NXR 3-38 210-250 kW	OES 355 LZ	210	3,50/60°S	10,0/22,5	35/42	59	10
		260	4,00/45°S	10,0/22			
NXR 3-39 250-290 kW	OES 355 LZ	315	5,00/60°S	10,0/23,0	48/62	50	1
		400	6,50/60°B	10,0/19,0	60/110	47	-2

Type	OES 255LE	OES 352 LE	OES 353 LZ	OES 354 LZ	OES 355 LZ
Referentie	400000111	400000115	400000318	400000319	400000320
Prijs (€)	990	1150	1560	1620	1951
Vermogen (kW)	65-125	77-166	94-217	142-275	126-430