

Temperature versus resistance table of the AF60:

<b>TO</b>	<b>Ohm</b>	<b>TO</b>	<b>Ohm</b>	<b>TO</b>	<b>Ohm</b>
-60	5458.15	-19	2314.15	22	489.59
-59	5413.31	-18	2237.75	23	471.39
-58	5366.14	-17	2162.46	24	453.81
-57	5316.57	-16	2088.37	25	436.83
-56	5264.53	-15	2015.54	26	420.78
-55	5209.95	-14	1946.45	27	405.27
-54	5152.80	-13	1878.67	28	390.30
-53	5093.02	-12	1812.24	29	375.84
-52	5030.57	-11	1747.20	30	361.89
-51	4965.42	-10	1683.60	31	348.88
-50	4897.55	-9	1622.76	32	336.30
-49	4829.56	-8	1563.36	33	324.16
-48	4759.04	-7	1505.41	34	312.43
-47	4686.01	-6	1448.94	35	301.10
-46	4610.49	-5	1393.95	36	290.46
-45	4532.51	-4	1342.21	37	280.18
-44	4455.06	-3	1291.87	38	270.24
-43	4375.44	-2	1242.94	39	260.64
-42	4293.72	-1	1195.41	40	251.37
-41	4209.98	0	1149.27	41	242.62
-40	4124.33	1	1106.19	42	234.17
-39	4039.94	2	1064.38	43	226.00
-38	3953.97	3	1023.83	44	218.10
-37	3866.53	4	984.53	45	210.47
-36	3777.77	5	946.46	46	203.29
-35	3687.81	6	910.75	47	196.35
-34	3599.94	7	876.16	48	189.64
-33	3511.24	8	842.68	49	183.15
-32	3421.83	9	810.28	50	176.88
-31	3331.86	10	778.94	51	170.80
-30	3241.50	11	749.40	52	164.94
-29	3153.81	12	720.83	53	159.26
-28	3066.02	13	693.22	54	153.78
-27	2978.28	14	666.53	55	148.48
-26	2890.73	15	640.75	56	143.52
-25	2803.51	16	616.60	57	138.72
-24	2719.79	17	593.26	58	134.08
-23	2636.62	18	570.72	59	129.59
-22	2554.12	19	548.95	60	125.25
-21	2472.41	20	527.93	61	121.24
-20	2391.59	21	508.43	62	117.36